



IMAGE COMING SOON






### KTSO30-PP-AS [↗](#)

#### Linear Ball Bearing and Housing Unit

Linear ball bearing and housing unit; open design, with self-aligning linear ball bearing, contact seals on both sides

### Technical information



#### Your current product variant


Size code	30
Seal	PP
Relubrication facility	AS

#### Technical data

	6	Ball rows
≈m	1,55 kg	Weight

#### Main Dimensions & Performance Data

F <sub>w</sub>	30 mm	Diameter of ball complement
H	60 mm	Height
L	142 mm	Length
B	87 mm	Width
C <sub>max</sub>	9.600 N	Load capacity dyn.
C <sub>0 max</sub>	12.000 N	Load capacity stat.



### Mounting dimensions

J <sub>B</sub>	68 mm	
Tol J <sub>B</sub>	+ 0,15 mm	Upper tolerance
Tol J <sub>B</sub>	- 0,15 mm	Lower tolerance
A <sub>5</sub>	43,5 mm	
Tol A <sub>5</sub>	+ 0,01 mm	Upper tolerance
Tol A <sub>5</sub>	- 0,01 mm	Lower tolerance
B <sub>2</sub>	14,3 mm	
J <sub>L</sub>	106 mm	Distance
Tol J <sub>L</sub>	+ 0,15 mm	Upper tolerance
Tol J <sub>L</sub>	- 0,15 mm	Lower tolerance
L <sub>6</sub>	54 mm	Distance
H <sub>2</sub>	35 mm	Center height
Tol H <sub>2</sub>	+ 0,008 mm	Upper tolerance
Tol H <sub>2</sub>	- 0,016 mm	Lower tolerance
H <sub>5</sub>	9,7 mm	
T <sub>5</sub>	22 mm	
H <sub>6</sub>	34 mm	
G <sub>2</sub>	M10	
N <sub>1</sub>	8,4 mm	
N <sub>4</sub>	2,5x5,3	
N <sub>3</sub>	15 mm	
K <sub>5</sub>	M8	
K <sub>8</sub>	NIP5MZ	Lubrication nipple
α	57 °	Angle