
**KGHA30-PP** [↗](#)

Linear Ball Bearing and Housing Unit

Linear Ball Bearing and Housing Units,
Sealed, Greased, Corrosion-resistant Design
Possible

Technical information

**Your current product variant**

| | | |
|-----------|----|--------|
| Size code | 30 | |
| Seal | PP | Sealed |

Main Dimensions & Performance Data

| | | |
|----------------|----------|---------------------|
| H | 67,5 mm | Height |
| B | 65 mm | Width |
| L | 59 mm | Length |
| | + 0,5 mm | Tolerance |
| C | 3.300 N | Dynamic load rating |
| C ₀ | 2.700 N | Static load rating |
| ≈m | 0,855 kg | Weight |

Mounting dimensions

| | | |
|--------------------|----------|-----------|
| H ₆ | 39 mm | |
| T ₅ | 20 mm | |
| J _B | 54 mm | |
| Tol J _B | ± 0,1 mm | Tolerance |
| G ₂ | M8 | |
| N ₁ | 6,7 mm | |
| N ₃ | 11,1 mm | |
| K ₅ | M6 | |



View product details on medias

13.06.2026, 14:16:14 UTC

SCHAEFFLER

Dimensions

| | | |
|--------------------|------------|-----------------------------|
| F _w | 30 mm | Diameter of ball complement |
| H ₂ | 35 mm | Axis center |
| Tol H ₂ | ± 0,015 mm | Tolerance |