



**KTHK16-B-PP-AS** [↗](#)

Linear Ball Bearing and Housing Unit

Linear ball bearing and housing unit; sealed, greased, with relubrication facility; corrosion-resistant design possible

Technical information




Your current product variant

Version	B
Seal	PP
Relubrication facility	AS

Main Dimensions & Performance Data

F _W	16 mm	Diameter of ball complement
H	36,5 mm	Height
L	65 mm	Length
B	43 mm	Width
C	1.440 N	Load capacity dyn. C
C ₀	1.240 N	Load capacity stat. C0
≈m	0,16 kg	Weight



Mounting dimensions

J _B	34 mm	
Tol J _B	+ 0,15 mm	Upper tolerance
Tol J _B	- 0,15 mm	Lower tolerance
B ₁	34 mm	
A ₅	21,5 mm	
J _L	40 mm	Distance
Tol J _L	+ 0,15 mm	Upper tolerance
Tol J _L	- 0,15 mm	Lower tolerance
H ₂	19 mm	Center height
Tol H ₂	+ 0,01 mm	Upper tolerance
Tol H ₂	- 0,014 mm	Lower tolerance
H ₄	28,1 mm	
H ₅	6,9 mm	
T ₅	11 mm	
H ₆	18 mm	
A ₃	13 mm	
G ₂	M5	
N ₁	4,3 mm	
N ₃	10 mm	
K ₅	M4	
K ₈	NIPA1	Lubrication nipple