
**KTBO40-PP-AS** [↗](#)

## Linear Ball Bearing and Housing Unit

Linear ball bearing and housing unit; open design, sealed, greased, with relubrication facility; corrosion-resistant design possible

## Technical information



## Your current product variant

Size code	40
Seal	PP
Relubrication facility	AS

## Main Dimensions &amp; Performance Data

$F_W$	40 mm	Diameter of ball complement
H	77 mm	Height
L	176 mm	Length
B	108 mm	Width
C	9.200 N	Load capacity dyn. C
$C_0$	9.900 N	Load capacity stat. C0
$\approx m$	3,56 kg	Weight



### Mounting dimensions

J <sub>B</sub>	80 mm	
Tol J <sub>B</sub>	+ 0,15 mm	Upper tolerance
Tol J <sub>B</sub>	- 0,15 mm	Lower tolerance
B <sub>2</sub>	18,2 mm	
J <sub>L</sub>	100 mm	
Tol J <sub>L</sub>	+ 0,15 mm	Upper tolerance
Tol J <sub>L</sub>	- 0,15 mm	Lower tolerance
H <sub>2</sub>	45 mm	Center Height
Tol H <sub>2</sub>	+ 0,015 mm	Upper tolerance
Tol H <sub>2</sub>	- 0,015 mm	Lower tolerance
A <sub>3</sub>	14 mm	
T <sub>5</sub>	34 mm	
H <sub>6</sub>	66 mm	
N <sub>1</sub>	13 mm	
N <sub>3</sub>	20 mm	
G <sub>2</sub>	M16	Thread size
G <sub>3</sub>	M8x1	Thread size
α	54 °	Angle
K <sub>5</sub>	M12	Screw DIN 6912